

FL-213M-DIP (3MP)

3MP IR 4MM DOME NETWORK CAMERA



KEY FEATURE

- Up to 3MP (2048 x 1536) resolution
- Progressive scan CMOS, capture motion video without incised margin
- Support dual stream, and long service life infrared LED
Approx. 10 to 30 meters IR range
- Two-way audio (-S)
- Audio I/O(-S)
- IR cut filter with auto switch
- PoE (Power over Ethernet)
- Ingress Protection level: IP66
- Impact Protection: IEC60068-2-75 test, Eh, 20J; EN50102, up to IK10

FL-213M-DIP	
Camera	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.07 lux @F1.2, AGC ON, 0 lux with IR
Shutter time	1/3s - 1/100,000s
Lens	4mm@ F2.0 (6mm, 12mm optional)
	1920 × 1080:Angle of view: 79°(4mm), 49°(6mm),
	23.2°(12mm)
	2048 × 1536: Angle of view: 70°(4mm),43.3°(6mm),
Lens mount	20.6°(12mm)
	M12
	IR cut filter with auto switch
	3D DNR
Wide dynamic range	Digital WDR
Compression Standard	
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 12 Mbps
Dual stream	Yes
Image	
Max. Image Resolution	2048 × 1536
Frame rate	50Hz: 20fps (2048 × 1536), 25fps (1920 × 1080),
	25fps (1280 × 720)
	60Hz: 20fps (2048 × 1536), 30fps (1920 × 1080),
	30fps (1280 × 720)
Image settings	Rotate mode,Saturation, brightness, contrast, sharpness
	adjustable through client software or web browser
BLC	Yes, zone configurable
ROI	Support
Network	
Network storage	Built in Micro-SD/SDHC/SDXC slot up to 128G, NAS (
	Support NFS,SMB/CIFS)
Alarm trigger	Line Crossing, Intrusion Detection, Motion detection,
	Tampering alarm, Storage exception
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,
	PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
System compatibility	ONVIF, PSIA, CGI,ISAPI
General functionalities	Flickerless, heartbeat, mirror, privacy mask, watermark, IP address
	filtering, Anonymous access Protocol
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
Reset Button	Yes
General	
Operating conditions	-30 °C ~ 60 °C (-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 5W (max. 7W with ICR switch)
Weather proof rating	IP66
IR range	20 to 30m
Dimension	60.4×76.9×139.28 mm (2.4" × 3.0" × 5.5")
Weight	500g (1.1 lbs)